Supporting Information for Two-Photon 3D Optical Data Storage via Aggregate Switching of Excimer-Forming Dyes

By *Joseph Lott*[±], *Christopher Ryan*[±], *Brent Valle*[±], *Jack R. Johnson III, David A. Schiraldi, Jie Shan, Kenneth D. Singer*[*] and *Christoph Weder*[*]

[±] These authors contributed equally to the present work.

Joseph Lott, Jack R. Johnson III, Prof. David A. Schiraldi, Prof. Christoph Weder,
Department of Macromolecular Science and Engineering, Case Western Reserve University
Cleveland, OH, 44106-7202, USA

Christopher Ryan, Brent Valle, Prof. Jie Shan, Prof. Kenneth D. Singer,
Department of Physics, Case Western Reserve University
Cleveland, Ohio 44106 USA
E-mail: kenneth.singer@case.edu

Prof. Dr. Christoph Weder
Adolphe Merkle Institute, Polymer Chemistry and Materials, University of Fribourg
Rte de l'Ancienne Papeterie, CH-1723 Marly 1, Switzerland
E-mail: christoph.weder@unifr.ch

Keywords: Photonics, Nonlinear Optics, Luminescence, Polymeric Materials



Figure S1. Normalized transmittance established in the Z-scan measurement of a C18-RG solution (0.025M in toluene) measured at 650 nm with a peak incident irradiance of 60 GW/cm^2. The solid line is a fit to an inverted Lorentzian model[32], which follows the on-axis irradiance of a focused Gaussian beam.



Figure S2. Intensity profiles of cross-sections taken along a straight line through the spots in the top row **of Figure 5**. a) Raw fluorescence between 650 and 800 nm (**Figure 5a**). b) Raw fluorescence between 500 and 525 nm (**Figure 5b**). c) Composite image from the ratio of the intensities of the two images (**Figure 5c**). d) Composite image with a low pass filter applied.